

Wilbergs Dust Stopper

HIGH-PENETRATION DUST - REPELLENT PRIMER

Dust - repellent primer in water dispersion specifically formulated for friable or dusty screeds, smoothing concrete or anhydrite screeds. **Product suitable for use with reactive glues, both monocomponent silane adhesives and bicomponent epoxy-polyurethane or polyurethane adhesives.**

TECHNICAL CHARACTERISTICS:

- Water-based monocomponent.
- Ready for use.
- Dust-repellent for concrete screeds.
- For indoor use.

WHERE IT CAN BE APPLIED:

- Traditional concrete screeds.
- Anhydrite screeds (plaster).
- Sub-floors with heating or cooling system.

DO NOT USE:

- On non-absorbent bases (glass, marble, tiles, etc.).
- On surfaces subject to continual rising damp that are not protected by a vapor seal barrier.

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Milky liquid
Viscosity, Ford 4 at 20 °C (seconds):	10 – 12
Dry (%):	13,5 – 15,5
Yield: (g/m ²):	100 – 150
Working life (minutes):	5 – 20
Usage temperature (°C):	+15 – +25
Time before use (days):	1 – 3
Film setting (hours):	3 – 5
Application/equipment:	Roller, brush
Equipment cleaning:	Water, before the products sets
Storage (months): Maximum temperature +5 °C	12
Disposal information:	Dispose of in compliance with the local and national regulations in force.
Packing:	10 kg
Recommendations for use:	Do not apply in damp environments Frost sensitive Always use suitable personal protective equipment Always consult the technical and safety information sheets Allow the product to reach 20 °C before applying

SURFACE PREPARATION:

Always use suitable tools to check the moisture content in the sub-floor. The sub-floor must be compact, free from moisture and with loose parts, such as chalk, dust, oil or wax residue cleaned off.

APPLICATION:

Allow the product to reach 20 °C before use. The product is ready for use. Apply evenly across the sub-floor with a roller or brush without piling up too much product in one place. Always check the moisture content of the screed before bonding <2% (<0.5% anhydrite).

Ambient temperature between 15 °C to 25 °C, relative humidity no greater than 75%. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

NOTES:

Avoid piling up too much product in one place as this may affect the adhesion of adhesives applied on top.

HAZARD PICTOGRAMS: non



The product is made in Italy for Wilbergs Group JSC.

Adesiv S.R.L Via delle Rose, 31 – 36061 Bassano del Grappa (VI) Tel. no. +39(0)424 566 406, www.adesiv.it
Adesiv S.R.L is a high quality adhesive manufacturer that has been producing adhesives since 1971.

Wilbergs Group JSC warrants that the information contained in this data sheet is based on the company's experience and technical/scientific knowledge; however, it cannot assume any responsibility for the results obtained from the use of the products, as the conditions of application are beyond the company's control. You should always check that the product is suitable for the specific use. This version supersedes and supersedes all previous versions.